

Product information – technical datasheet

Jan. 2025



AdBlue® = registered trademark of VDA

AdBlue®

Parameter	Specification		Unit	Test Method
	min.	max.		
Urea content	31,8	33,2	%	ISO 22241-2:2019, Annex C
Refractive index at 20°C	1,3814	1,3843	-	ISO 22241-2:2019, Annex C
Alkalinity as NH ₃	-	0,2	%	ISO 22241-2:2019, Annex D
Biuret	-	0,3	%	ISO 22241-2:2019, Annex E
Aldehydes	-	5	mg/kg	ISO 22241-2:2019, Annex F
Insoluble	-	20	mg/kg	ISO 22241-2:2019, Annex G
Phosphate (PO ₄)	-	0,5	mg/kg	Calculated from P ISO 22241-2:2019, Annex I
Calcium	-	0,5	mg/kg	
Iron	-	0,5	mg/kg	
Copper	-	0,2	mg/kg	
Zinc	-	0,2	mg/kg	
Chromium	-	0,2	mg/kg	
Nickel	-	0,2	mg/kg	
Aluminium	-	0,5	mg/kg	
Magnesium	-	0,5	mg/kg	
Sodium	-	0,5	mg/kg	
Potassium	-	0,5	mg/kg	
Identität	Identical to the comparison pattern			ISO 22241-2:2019, Annex J

Sampling and testing according to ISO 22241-2:2019 Annex A

The aforementioned data shall constitute the agreed contractual quality of the product at the time of passing of risk. The data are controlled at regular intervals as part of our quality assurance program. Neither these data nor the properties of product specimens shall imply any legally binding guarantee of certain properties or of fitness for a specific purpose. No liability of ours can be derived therefrom.

Advanced Blue Technologies GmbH

Sieveringer Straße 184

1190 Wien

Austria

Raiffeisenbank Region Amstetten eGen: IBAN: AT93 3202 5000 0505 1305 | BIC: RLNWATWWAMS

Tel: +43 (0)1 343 11 78 78 – 0

E-Mail: office@austromol.at

www.austromol.at

Firmenbuchgericht: Wien

Firmenbuch-Nr.: FN 539125g

UID-Nummer: ATU75886347

EORI: ATEOS1000119936